

アセチレンガス用火口詳細

SA100 00溶接火口



取付ネジピッチ	M6×1.0
材質	黄銅
表面処理	脱脂処理

品番	先端穴 (mm)	能力番号	寸法図
SA100-50	0.7	50	
SA100-70	0.8	70	
SA100-100	0.9	100	
SA100-140	1.0	140	
SA100-200	1.2	200	
SA100-225	1.3	225	
SA100-250	1.4	250	
SA100-315	1.5	315	
SA100-400	1.6	400	
SA100-450	1.7	450	
SA100-500	1.8	500	

SA102 00ロング火口



取付ネジピッチ	M6×1.0
材質	黄銅
表面処理	脱脂処理

品番	先端穴 (mm)	能力番号	寸法図
SA102-50	0.7	50	
SA102-70	0.8	70	
SA102-100	0.9	100	
SA102-140	1.0	140	
SA102-200	1.2	200	
SA102-225	1.3	225	
SA102-250	1.4	250	
SA102-315	1.5	315	
SA102-400	1.6	400	
SA102-450	1.7	450	
SA102-500	1.8	500	

SA110 B-00溶接火口



取付ネジピッチ	3/16×W24
材質	黄銅
表面処理	脱脂処理

品番	先端穴 (mm)	能力番号	寸法図
SA110-100	0.9	100	
SA110-140	1.0	140	
SA110-200	1.2	200	
SA110-225	1.3	225	
SA110-250	1.4	250	
SA110-315	1.5	315	

SA200 小型溶接火口



取付ネジピッチ	M8×1.0
材質	黄銅
表面処理	脱脂処理

品番	先端穴 (mm)	能力番号	寸法図
SA200-50	0.7	50	
SA200-70	0.8	70	
SA200-100	0.9	100	
SA200-140	1.0	140	
SA200-200	1.2	200	
SA200-225	1.3	225	
SA200-250	1.4	250	
SA200-315	1.5	315	
SA200-400	1.6	400	
SA200-450	1.7	450	
SA200-500	1.8	500	

SA210 中型溶接火口



取付ネジピッチ	M8×1.0
材質	銅
表面処理	脱脂処理

品番	先端穴 (mm)	能力番号	寸法図
SA210-200	1.2	200	
SA210-225	1.3	225	
SA210-250	1.4	250	
SA210-315	1.5	315	
SA210-400	1.6	400	
SA210-450	1.7	450	
SA210-500	1.8	500	
SA210-630	2.0	630	